









PIG® Water-Activated Flood Barrier

WTR051 5.2m x 22cm x 6mm

These barriers swell on contact with water to become a strong, sturdy barrier that you can rely on for protection from floodwater.

- Block floodwater by laying this 5.2m long water-activated flood barrier in front of your driveway, garage or door
- Customise by stacking in pyramid formation to increase flood-prevention height; lay multiple barriers end to end and adjust as needed for your location
- Move and handle easily; unlike sandbags, these barriers are lightweight and compact before wetting
- Leave activated barriers in place for up to six months, as long as they stay saturated
- NOTE: not for use with salt water and not to be driven over

Dimensions When Fully Saturated	21cm W x 5.2m L x 7cm H When Fully Saturated
Height When Fully Saturated	7cm When Fully Saturated
Ideal For	Stacking, Retaining Walls
Weight When Fully Saturated	40kg each When Fully Saturated
Colour	Black
Dimensions	5.2m W x 22cm L x 6mm H
Fluids Absorbed	Water-based liquids
Absorbency	Up to 198.5 L per package
Temperature Limit	Works from 0°C (32°F) to 82°C (180°F)
Sold as	5 per package
Weight	2.85 kg
# per Pallet	84
Composition	Polypropylene outer fabric; Super Absorbent Polymer (SAP) Pulp filler
Capacity	39.7ltrs per Bag

Technical Documents

Instructions for PIG Water-Activated Flood Bags & Barriers

Technical Data Sheet for PIG® Water Activated Flood Barriers

FAQ for PIG Water-Activated Flood Bags & Barriers

Disclaimers

Saltwater Notice

Not for use with saltwater.

New Pig
World's best stuff for leaks, drips and spills.

Hogs Hill • Watt Place • Hamilton International Technology Park • Blantyre • Glasgow • G72 0AH
0800 919 900 • newpig.co.uk • pigpen@newpig.com