











FLME135 Not for Chemical Contact, Not for Oil/Grease Contact, 91cm x 9.4mm

Economical mat provides comfort and traction in light-duty applications.

- Recommended for light-duty use in dry industrial environments
- Pebble pattern provides non-directional traction and is easy to clean
- Constructed of micro-cellular vinyl consisting of millions of air bubbles to provide basic worker comfort
- Sold per metre, you can customize your mat length to your workplace with clean, factory-cut edges; maximum full roll length is 18.3m
- All 4 sides are bevelled and sealed to minimise tripping hazards
- Available with yellow borders along sides for added safety
- Slip resistance R10 according to DIN51130 and BG-rule BGR181
- Fire rating Class 2 according to NFPA Safety Code 101
- Free of DOP, DMF, ozone depleting substances, silicone, and heavy metals; safe for vehicle painting facilities











Specifications

Static Dissipative

Dimensions	91cm W x 9.4mm H
Bevelled Edge	Yes
Grit Surface	No
Modular	No
Safe for Welding Areas	No
Sold as	1 each
Weight	2.4 kg
Composition	PVC
Application	Dry Applications
Chemical Contact	Not for Chemical Contact
Oil/Grease Contact	Not for Oil/Grease Contact

No

Water Contact Non-Draining

Technical Information

Certifications, Approvals and Ratings

DIN51130 - R10,BGR181 - R10



Hogs Hill • Watt Place • Hamilton International Technology Park • Blantyre • Glasgow • G72 0AH 0800 919 900 • newpig.co.uk • pigpen@newpig.com