

# ToughDeck Workplace Modular Tiles

FLME171 For Wet Applications, 48cm x 48cm x 20mm



Non-slip interlocking decking for is ideal for wet working environments.

- Recommended for heavy-duty use in wet industrial environments indoors
- Manufactured from 100% recycled rubber and plastic
- Combination of substantial product height and large holes offers excellent drainage
- Can be installed into almost any configuration to protect nearly any size or shape floor
- Easy installation and connectivity with connector system that conceal joins
- An economical yet heavy-duty matting solution
- Ideal for industrial use, especially in areas prone to liquid spillage
- Edges and Corner Edges (sold separately) add a finished bevelled edge that helps prevent trips and falls
- Slip tested to DIN 51130 - R10



Heavy Traffic



Insulation



Protection



Drainage



Oil Resistant



Tiles



Anti Fatigue



Antislip



## Specifications

|                        |                                    |
|------------------------|------------------------------------|
| Colour                 | Black                              |
| Dimensions             | 48cm W x 48cm L x 20mm H           |
| Recycled Content       | 100% Post-Consumer Recycled Rubber |
| Bevelled Edge          | Yes                                |
| Grit Surface           | No                                 |
| Modular                | Yes                                |
| Safe for Welding Areas | No                                 |
| Sold as                | 1 each                             |
| Weight                 | 1.95 kg                            |
| Composition            | Recycled rubber & plastic          |
| Application            | Wet Applications                   |
| Chemical Contact       | Not for Chemical Contact           |
| Oil/Grease Contact     | For Heavy Oil/Grease Contact       |
| Static Dissipative     | No                                 |
| Water Contact          | Draining                           |