

## **Workstation Mat**

FLME234 For Wet Applications, 100cm x 150cm x 12mm

Workstation Mat relieves worker fatigue and increases traction. Large 22mm x 22mm drainage holes make it perfect for wet and oily industrial environments where liquid and swarf gathers.

- Recommended for medium duty use in wet industrial environments, suitable for frequent oil spills
- Interwoven, loose lay PVC mat resists many oils, greases, mild acids and alkalis so it can be used in a variety of industrial settings
- Moulded bevel edges on all four sides are bevelled to prevent tripping on the mat
- Hard-wearing flexible PVC extrusions are cross-ribbed in both directions; adds traction for safer footing, as well as enhanced mat durability
- Flexible PVC construction provides anti-fatigue properties; helps increase worker comfort and productivity
- 22mm x 22mm drainage holes provide aeration and allow fluids and debris to fall through, leaving a dry and tidy top surface
- Ideal for production lines, assembly areas, workbenches, machine shops, packaging areas and more
- Slip resistance R10 according to EN 13552
- Fire tested to DIN 54332 (B2) part of DIN 4102





















## **Specifications**

Colour	Black with yellow border
Dimensions	100cm W x 150cm L x 12mm H
Bevelled Edge	Yes
Grit Surface	No
Modular	No
Safe for Welding Areas	No
Sold as	1 each
Weight	6.7 kg
Composition	PVC

Application	Wet Applications
Chemical Contact	For Heavy Chemical Contact
Oil/Grease Contact	For Heavy Oil/Grease Contact
Static Dissipative	No
Water Contact	Draining

## **Technical Information**

## **Certifications, Approvals and Ratings**

Conforms to Slip Resistance Test EN 13552 Category R10, Fire tested to DIN 54332 (B2) part of DIN 4102



Hogs Hill • Watt Place • Hamilton International Technology Park • Blantyre • Glasgow • G72 0AH 0800 919 900 • newpig.co.uk • pigpen@newpig.com