



Workstation Mat

FLME235 For Wet Applications, 120cm x 180cm x 12mm

Workstation Mat relieves worker fatigue and increases traction. Large 22mm x 22mm drainage holes make it perfect for wet and oily industrial environments where liquid and swarf gathers.

- Recommended for medium duty use in wet industrial environments, suitable for frequent oil spills
- Interwoven, loose lay PVC mat resists many oils, greases, mild acids and alkalis so it can be used in a variety of industrial settings
- Moulded bevel edges on all four sides are bevelled to prevent tripping on the mat
- Hard-wearing flexible PVC extrusions are cross-ribbed in both directions; adds traction for safer footing, as well as enhanced mat durability
- Flexible PVC construction provides anti-fatigue properties; helps increase worker comfort and productivity
- 22mm x 22mm drainage holes provide aeration and allow fluids and debris to fall through, leaving a dry and tidy top surface
- Ideal for production lines, assembly areas, workbenches, machine shops, packaging areas and more
- Slip resistance R10 according to EN 13552
- Fire tested to DIN 54332 (B2) part of DIN 4102



Medium Traffic



Anti Fatigue



Antislip



Protection



Insulation



Drainage



Jet Wash



Oil Resistant



Fire Retardant

Specifications

Colour	Black with yellow border
Dimensions	120cm W x 180cm L x 12mm H
Bevelled Edge	Yes
Grit Surface	No
Modular	No
Safe for Welding Areas	No
Sold as	1 each
Weight	9.7 kg
Composition	PVC

Application	Wet Applications
Chemical Contact	For Heavy Chemical Contact
Oil/Grease Contact	For Heavy Oil/Grease Contact
Static Dissipative	No
Water Contact	Draining

Technical Information

Certifications, Approvals and Ratings

Conforms to Slip Resistance Test EN 13552 Category R10, Fire tested to DIN 54332 (B2) part of DIN 4102



Hogs Hill • Watt Place • Hamilton International Technology Park • Blantyre • Glasgow • G72 0AH
0800 919 900 • newpig.co.uk • pigpen@newpig.com